

PRODUCT DESCRIPTION

ProCoat Floor Stripper is a ready to use floor stripper designed to reduce time and labor by quickly removing floor finishes, dirt, grime, oil, stains, tar, gums, adhesives and scuffmarks.

ProCoat Floor Stripper can be used "as-is" for older, heavier finishes. Or, it can be diluted for lighter finishes.

- Water-soluble
- Low-sudsing
- Homogenous
- Uniform consistency
- Use with soft or hard water
- Contains no abrasives

Intended Uses:

- Vinyl Composition Tile
- Resilient and Mineral Floorings
- Rubber Flooring
- Hospitals, Assisted Living, Institutions
- Processing Plants and Pharmaceutical
- Transportation: Trains, Buses & Planes
- Education, Hospitality Industry
- Commercial and Industrial properties

PRODUCT CHARACTERISTICS

Appearance and color:

Clear liquid

Flash Point:

Non-flammable

Dilution Ratio:

1:1 mixing ratio (1 part **ProCoat** to 1 part clean, fresh water)

Shelf Life:

18 months, unopened when properly stored. Re-inspect after 1 year.

Storage:

45°F-70°F -- Keep from freezing or prolonged exposure to sunlight and heat. Keep closed during storage.

Reducer:

Use clean, fresh water.

Coverage Rate:

Coverage rate is dependent on application method and substrate. Below figure is for estimation purposes only. Testing should be completed for accurate figures: 200 sq.ft./gallon per coat.

Equipment Needed:

Non-shed mop, floor scrubbing machine, wet vacuum.

SYSTEM OPTIONS / COMPATABILITY

Vinyl Tile or Sheeting: ProCoat Floor Stripper
ProCoat Clear Top Coat

Vinyl Tile, Sheeting or VAT: ProCoat Floor Stripper
ProCoat Base Coat
ProCoat Clear Top Coat

Rubber Flooring & Base: ProCoat Floor Stripper
ProCoat Clear Top Coat

PHYSICAL PROPERTIES

Free Acid: Less than .50% when tested in accordance with ASTM D460

PH Value (undiluted): 11.5

Amonia Content: Less than 3% as NH₃ by weight when tested in accordance with ASTM D 500

Viscosity: No greater than "H" at 25°C when compared to the Gardner Bubble Viscometer Standards in accordance with ASTM D 1545

Solubility: Completely soluble in distilled water

Rinsing Properties: Free rinsing when tested as specified in ASTM D 3494, except use 100 ml rinses of hard water (300 ppm CaCO₃ and use manufacturer's dilution)

Floor Finish Removal Efficiency: tested in accordance with ASTM D 1792, except pre-soak the test tiles in the diluted stripper for 15 minutes immediately prior to scrubbing.

PACKAGING INFORMATION

Packaging: 4 gallons per case
5 gallon pail
55 gallon drum

Weight: 1 gallon = 9 lbs
1 case = 36 lbs
5 gallon pail = 45 lbs
55 gallon drum = 500 lbs

Class 55

CONTACT INFORMATION

For further technical questions or warranty issues, please call D&D Professional Coatings at (614) 487-1527: