



ANTI-GRAFFITI COATING SYSTEM SPECIFICATIONS

PRODUCT NAME:

Graffiti Melt Coating is a zero VOC, nontoxic, biodegradable, paraffin-based emulsion.

Graffiti Ease Away Remover is a nontoxic remover designed to clean graffiti from coated, baked and delicate surfaces.

Graffiti Terminator Remover is a nontoxic remover designed to clean graffiti from metal, some brick and coated surfaces.

PRODUCT DESCRIPTION:

Graffiti Melt Coating is a ready-to-use, low odor, "sacrificial" coating used to protect exterior surfaces from graffiti, posters and atmospheric pollution. Graffiti Melt Coating is composed of water and food grade materials, and, creates a tough barrier without altering the appearance or texture of the treated surface.

Once the surface is coated, graffiti can be removed with either a hot water pressure washer or with Graffiti Ease Away or Graffiti Terminator Remover and cold water. Simply re-apply the coating to the area that has been removed.

Uses:

- * Concrete
- * Aggregate
- * Stucco
- * Painted Surfaces
- * Buildings, walls, light poles, bridges, fences, trees, and many other surfaces.
- * Brick
- * Block
- * Wood

Performance:

- * Graffiti Resistant
- * Non-flammable
- * Fast drying
- * USDA Compliant
- * Odorless
- * Breathable
- * Zero VOC
- * Solvent Free

CHARACTERISTICS:

- Color:** Clear
- Finish:** Satin
- Reduction:** None
- Curing Mechanism:** Evaporation

***Graffiti Melt Coating and Removers** meet all current standards of the U.S. Environmental Protection Agency as well as meets or exceeds all known EPA, OSHA, and CARB hazardous material requirements for this class of architectural coatings.

TECHNICAL DATA:

Resin Type: Paraffin Wax
% Solids by volume: 30%
Dry Time:
 (Temperature & Humidity Dependent)
@ 45°F & 75%RH @ 1 mil wet:
 To Touch: 25 minutes
 Tack-free & Recoat: 45 minutes
 Dry Hard: 1 hour
@ 75°F & 50%RH @ 1 mil wet:
 To Touch: 5 minutes
 Tack-free & Recoat: 15 minutes
 Dry Hard: 45 minutes
Full Cure: 24 hours
Dry Film: <1 mil
VOC: 0
Flash Point: None
pH: 9.3
Specific Gravity: 0.98 Kg/l
Flexibility: Slight
Solubility in Water: Complete
Breathable: Yes
Viscosity: D-816 31 sec @77°F
Odor: Light pine
EPA Compliant: Yes
CARB Compliant: Yes

SHIPPING DATA:

Packaging:
Graffiti Melt Coating:
 One (1) Gallon, Five (5) Gallon Pails, and 55 Gallon Polyethylene Drums.
Graffiti Ease Away Remover:
 22oz. Sprayer Bottles, One (1) Gallon, and 55 Gallon Polyethylene Drums.
Graffiti Terminator Remover:
 One (1) Gallon and 55 Gallon Polyethylene Drums

Shipping Weight (approximate): lbs.
 22 oz. Sprayer (12/case) 20 lbs.
 Gallons (4/case) 36 lbs.
 Five Gallon Pail 45 lbs.
 55 Gallon Drum 465 lbs.

Shipping Classification: 55

TECHSPEC

The Tech-Spec Data Sheet conforms to editorial style prescribed by the Constitution Specifications Institute. The manufacturer is responsible for technical accuracy.

STORAGE:

Graffiti Melt Coating should be stored at a temperature above 50°F and not be allowed to freeze. Preventative measures are necessary for both transporting and storage. Any material that has been frozen must be discarded.

Containers should be shaken before used and kept closed during storage. The material will withstand storage temperatures up to 140°F, but avoid prolonged exposure to sunlight.

Shelf Life:

18 months, unopened @ 50°F to 90°F.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS!

LIMITATIONS:

*Graffiti Melt should not be applied in high wind, rain or where rain is imminent, or where surface temperatures are below 45°F.

*Desired surface pH level between 8.0 and 10.0.

*Retaining walls, planter boxes or surfaces where water will be of concern must be waterproofed.

*Slippery when wet if applied to horizontal surfaces.

*Does not promote or prevent efflorescence.

*A heavier coat will cause over coating or yellowing.

*HVAC runoff can sometimes adhere to the coating to cause streaking.

COVERAGE:

The following coverage rates are approximate and for estimating purposes only. Test applications on actual surfaces to accurately determine effective coverage. Porosity, texture, method of application, and climate conditions affect coverage rates.

Graffiti Melt Coating Coverage		
Read as square feet per gallon per coat.		
Sq.Ft.	Substrate	Coats
600	Metal	1
450	Sealed Wood & Concrete	1
400	Concrete & Painted Block	2
350	Brick	2
300	Concrete Block & Stucco	2